

TECHNICAL DATA SHEET

Product Description

PP - L5D98 Which is produced by CHN Group Baotou Chemical Co., Ltd, based on The the UnipolTM gas phase process technology of grace company to produce homopolymer polypropylene resin. The main raw material of the product is polymerization grade propylene, which is produced by polymerization, degassing, granulation, packaging and other processes with efficient catalyst.





Product Specification

No.	Property			Units	PP-H, F, 118-03-030 (L5D98)		
NO.					Premium	First	Qualified
1	Appearance	Coloring granule		pcs/kg	≤10	≤20	≪30
		Black granule		pcs/kg	0		
		Large granule and small granule		g/kg	Report		
2	Melt Mass-Flow Rate		Standard Value	g/10min	3. 4		
			Deviation		± 0.5	± 0.8	±0.8
3	Isotactic Index		Standard Value	%	95		
5			Deviation	70	± 2	± 3	
4	Total Ash, (mass)			mg/kg	≤300	≪400	
5	Tensile Stress at Yield			MPa	≥28.0		
6	Fish eye		0. 4mm	pcs/1520c	≤5		
	count		0.8mm		≤30		
7	Yellowness Index				≤4		
8	Haze			%	Report		

Features

• Excellent ductility

Applications

• BOPP FILM

- \bullet Excellent bending fatigue resistance, heat resistance
- ${\boldsymbol \cdot}$ High tensile strength and surface hardness
- Good resistance to environmental stress cracking